



ARMORDeck

with Cable Channels



Module Size	42" x 42" (1.067m x1.067m) usable surface area 45"x 45" outside dimension w/connection tabs exposed
Cable Channel	Bi-directional cable channel - top access 4" x .75" at highest point (.71" at lowest point)
Thickness	2" (5.08cm)
Colors	Desert Beige, Light Gray, Dark Gray. Custom colors available.
Edging	Sloped transitional pieces with traction 41-7/8"(L) x 12"(W) x 1-7/8"(at highest point) Weighs 12 lbs. Secure edging to modules with a cam lock.
Warranty	3 year manufacturer's limited warranty, including CAM locks
Ground Surface	ArmorDeck™ is engineered for use over natural or synthetic turf, dirt, sand, gravel, asphalt, and other sensitive surfaces. It is ideal for ground protection and access.

CONNECTION SYSTEM:

Integrated self-aligning hook and loop connection system. Additional cam-lock system can be employed when added strength is required

Cam Locks Rotating proprietary plastic cam locks for added strength.

Connection Loops Four (4) built-in connector loops on each side and four (4) receiver pins on each side. Connection systemsigned to connect easily by allowing panels to nest into each other. Reinforcement ribbing behind connector loops incorporated into main panel design.

PANEL CONSTRUCTION:

Durable panel construction including high grade materials, engineered structural support and high quality manufacturing

Material High-Density Polyethylene (HDPE) reinforced with additives for added strength, flex modulus, and izod impact value.

UV Package A 5-year UV package is incorporated into the material formulation to prevent degradation and brittleness as a result of prolonged sun exposure.

Understructure Bi-directional ribbing system which includes four (4) full-height ribs in either direction and five (5) half-height ribs, thus providing strength while minimizing surface area contact. All ribbing incorporates radius edges to prevent sub-surface damage or cutting.

Liquid Containment Panels overlap upon connection to minimize liquid penetration. Overlap incorporates a specialized containment channel under each overlap area, designed to capture stray liquid that may seep from top surface.

Underside Module Optional underside module attaches to the underside of each panel, thus sealing the system and providing additional strength, rigidity and weight distribution to allow for more heavyweights loading. ArmorDeck systems interconnect to each other to allow for multiple versions of Armor-Deck to be seamlessly connected as needed for varying applications.

Aeration Holes Specially designed to allow light, aeration, and rain drainage. Incorporates proprietary ridge that surrounds each aeration hole, thus preventing casual spills from flowing through to the subsurface. Specialized aeration hole ridge also provides additional traction during wet conditions.

WEIGHT LOADING:

Weight		Weight Capability
Module w/o Bottom	31 lbs 14.1 kg	25,000 lbs / sq ft*
Module w/ Bottom	41 lbs / 18.6kg	45,000 lbs / sq ft*

*static load on a solid and level subsurface

FIRE RATING: UL94 HB

